

Pro Zone 45000 Thermostats

JOB		REPRESENTATIVE	
ENGINEER		ORDER #	DATE
CONTRACTOR		SUBMITTED BY	DATE
PAGE #		APPROVED BY	DATE

Qty	Part #	description	Comments
	450008	Basic electronic stat	
	450009	Basic dual sensing stat w/probe	
	450010	Didgital dual sensing stat w/probe	
	450011	Chronotherm stat	

Pro Zone 45000 Thermostats

Measured temperature precision 0.2°F, Operating Temperature 32°F -122°F, Setting Temperature Range 41°F- 86°F, Floor Limiting Temperature Range 50°F- 104°F.

Pro Basic electronic stats combine versatility with ease of use. tempera-
ture is controlled via a calibrated dial. Units come w/ or w/o external
sensor. External sensor can be programmed to limit floor temperature
supply. Stats work with ProZone actuators and ProZone Modules. Pump
or other Aux output via TRIAC (15VA, 24VAC). Regulation through Pro-
portional (PI) algorithm.



450008 / 450009

Pro Digital series stats feature a digital display of actual and targeted
temperature. They can be programmed for day and night time reduc-
tion. Cooling reverses the limiting function of the stat . Works with
external and internal sensors. Stats work with ProZone actuators and
ProZone Modules. Pump or other Aux output via TRIAC (15VA, 24VAC).
Regulation through Proportional (PI) algorithm.



450010

Pro Chronotherm is a timer programmable Stat with 24/7 daily/weekly
program. Stat includes a built-in relay (8A, 24VAC) for circuit pump or
other functions Operating temperature 32°F-122°F, Comfort/Reduc-
tion mode setting temperature range 41°F-95°F, Power Supply 2-AA
batteries.



450011