


PVC/ABS TRANSITION SOLVENT CEMENT

ABS to PVC Transition Joint Cement - White

PRODUCT DESCRIPTION

PVC/ABS TRANSITION (White) is a regular bodied cement for PVC to ABS transition joints. CSA certified for non-pressure applications. Meets ASTM D-3138 requirements. Recommended for pipe up to 6" (152 mm) in diameter. Use with our approved 3 PRIMER or 3V PRIMER to prime the PVC components, it is not necessary to prime the ABS components.



DIRECTIONS FOR USE

Applying the Cement will require the use of Primer and following the step-by-step procedure for cutting the pipe and preparing the surfaces. These procedures are set out in detail on the Cement and Primer container labels.

PACKAGING

The PVC/ABS TRANSITION Solvent cement is packaged in a variety of metal container sizes and types, which include the screw top cans with an applicator dauber attached.

SAFETY DATA

It is extremely important to read the relevant safety data in the WHMIS section of the label and the relevant Material Safety Data Sheet, before using the product.

TYPICAL PROPERTIES

APPEARANCE:	White regular bodied liquid
VISCOSITY RANGE:	180 - 200 cps at 23°C
FLAMMABILITY:	Extremely flammable
ODOUR:	Strong Ketone Odour. Use in well-ventilated areas
SOLVENTS:	Tetrahydrofuran and Methyl Ethyl Ketone (MEK)
SPECIFIC GRAVITY:	0.90 to 1.00
FREEZING POINT:	<0°C
SHELF LIFE:	Approximately twelve months in tightly closed containers
FLASH POINT:	- 5°C TAG Closed Cup.
VOC INFORMATION:	This product emits VOC's (volatile organic compounds) in its use. Always ensure that the use of this product complies with local VOC Emission Regulations, where they exist. <u>The VOC level is 550 grams/litre (SCAQMD Test Method 316A)</u>