

VesiPEX

Versatility, Reliability & Flexibility

VesiFlow™ PEX-c Tubing

Versatility, Reliability and Flexibility is VesiFlow PEX-c tubing.

The unique properties of VesiPEX's VesiFlow PEX-c offer distinct performance advantages over the competition. It delivers ease of use because of its versatility in fitting options as well as flexibility and long-term strength. PEX-c has a comparable flexibility to that of PEX-a but, without the chemical byproducts produced during the cross-linking procedure.

The irradiation method of cross-linking used in the manufacture of PEX-c tubing imparts extraordinary resistance to chemicals. It provides superior odor and taste properties through increased material stability. VesiFlow PEX-c can withstand high temperatures, erosion, corrosion, expansion, contraction, abrasion, high pressure and water hammer. Every coil is tested to ensure proper cross-linking percentage (75% - 89%).



PEX-c tubing is the most environmentally friendly PEX tubing available. PEX-c unlike the other types (PEX-a & PEX-b) creates no chemical byproducts during the cross-linking process.

Listings and Approvals

- NSF Standard 61: Drinking Water System Components - Health Effects
- NSF Standard 14: Drinking Water System Components - Performance
- Plastic Pipe Institute (PPI) Hydrostatic Stress Board, TR-4/2000 Listing, Standard Grade @ 73° F. (23° C.) HDB 1250 psi, 180° F. (83° C.) HDB 800 psi and 200° F. (93° C.) HDB 630 psi.
- CSA Standard B137.5 - Cross-linked polyethylene (PEX) tubing for pressure applications
- CSA Standard B125.93 - Plumbing Fittings, Certificate of Compliance
- U.P. Code
- NSF CI-TD Chlorine Resistance Performance for Potable Water Applications
- ASTM F876-04: Standard Specification for Crosslinked Polyethylene (PEX) Tubing
- ASTM F877-05: Standard Specification for Crosslinked Polyethylene (PEX) Tubing - hot and cold water Distribution Systems
- ASTM F1960, F2080, F1807, F2098 & F2159

304 STONE RD. UNIT 536
GUELPH, ON N1G 4W4
(844) 652-8739
INFO@VESIPEX.COM

www.vesipex.com