


# MASTERS<sup>®</sup>


## ORANGE -TAPE


### Premium Quality Thread Sealing Tape



FOR USE ON THREADED JOINTS OF METAL PIPE (NOT EXCEEDING 3 INCH NPS)  
IN ASSEMBLIES HANDLING GASOLINE, PETROLEUM OILS, NATURAL GAS,  
PROPANE AND BUTANE PRESSURE NOT OVER 15514 kPa / 2200 psi

MASTERS<sup>®</sup> ORANGE  -TAPE seals all metal and plastic threaded connections against leakage at temperatures from -400°F to +600°F (-240°C to +316°C).


MASTERS<sup>®</sup> ORANGE  -TAPE is non-corrosive, non-flammable, clean, easy to use and is available in a wide range of widths and lengths. Joints disassemble easily, even after years of service.

Because it is chemically inert, MASTERS<sup>®</sup> ORANGE  -TAPE is impervious to virtually everything including:

#### Directions:

- Make sure threads are clean and remove any shreds of previously applied tape.
- Beginning with the first thread of the male end, wrap tape in the direction of the thread spiral. Use enough for a good seal.
- Tighten the joint using a wrench.

- Acids & Alkalis
- Air
- Ammonia
- Chlorine
- CO<sub>2</sub>
- Fuels
- Gasoline
- Hydrocarbons
- Kerosene
- Natural Gas (ULC Tape Only)
- Nitrogen
- Oxygen
- Refrigerants (most)
- Solvents
- Steam
- Water

Catalogue Number	Description	Quantity per Case	Approximate Case Shipping Weight		
TOA260	1/4" x 260" (0.63 cm x 6.6 m) Roll	12	0.6 lbs	0.3 kg	
TOD540	1" x 540" (2.54 cm x 13.72 m) Roll	12	2 lbs	0.9 kg	
* 	ULC260	1/2" x 260" (1.27 cm x 6.6 m) Roll	12	0.7 lbs	3 kg
	ULC540	1/2" x 540" (1.27 cm x 13.72 m) Roll	12	1 lb	0.5 kg
	ULC540V	1/2" x 540" (1.27 cm x 13.72 m) Roll	100	8 lbs	3.6 kg
	ULC1296	1/2" x 1296" (1.27 cm x 32.94 m) Roll	12	2 lbs	0.9 kg
	ULC1296V	1/2" x 1296" (1.27 cm x 32.94 m) Roll	100	17 lbs	7.7 kg
	TOC540	3/4" x 540" (1.91 cm x 13.72 m) Roll	12	2 lbs	0.9 kg

## G. F. THOMPSON CO. LTD.

The professional choice since 1947

1-800-499-3673

www.gfthompson.com

Canada



Meets MIL SPEC  
A-A-58092  
(superseding  
T-27730A)

\*   
Listed by Underwriter's Laboratories  
of Canada and the U.S.  
For up to 3" pipe.

2015