

PVC-PRO

MEDIUM BODIED, FAST SETTING PVC SOLVENT CEMENT

MASTERS® PVC-PRO solvent cement is ideal for joining all schedules and classes of PVC pipe and fittings up to 6" in diameter with interference fit.

MASTERS® PVC-PRO is Low VOC and meets South Coast Quality Management District (SCAQMD) 1168/316A or BAAQMD Method 40 requirements, as well as ASTM D2564.

MASTERS® PVC-PRO is recommended for use on potable water, pressure pipe, conduit or DWV, and is available in Clear or Grey.

Directions:

- · Cut pipe ends square, chamfer and clean pipe ends.
- Check dry-fit of pipe and fitting. Pipe should easily go 1/3 of the way into the fitting. If pipe bottoms, it
- Use a suitable applicator at least ½ the size of the pipe diameter.
- Clean and prepare pipe and fitting with a listed Cleaner and/or Primer, where local code requires.
- Apply a liberal coat of cement to pipe, approximately the depth of the socket. Leave no uncoated surface.
- Apply a coat of cement to the inside of the fitting, avoid pooling or puddling of cement.*
- Apply a second coat of cement to the pipe.
- Assemble parts quickly as cement must be in a fluid state when joining.
- Push pipe fully into the fitting using a 1/4 turning motion until the pipe bottoms.
- Hold pipe and fitting together for 30 seconds to prevent pipe push-out (longer in lower temperatures).
- Wipe off excess cement for a clean esthetic appearance.
- Allow cement to fully cure before pressure testing. Longer cure times may be required at lower temperatures or for larger diameter piping.









ASTM D2564, NSF Standard 14 for PW, DWV and Sewer, IAPMO Listed

Catalogue Number	Description	Quantity Per Case	Approximate Case Shipping Weight	
PVC250-G	Masters® PVC-Pro Medium Grey Cement - 237 mL	24	14.5 lbs	6.5 kg
PVC500-G	Masters® PVC-Pro Medium Grey Cement - 473 mL	24	27.5 lbs	12.5 kg
PVC1L-G	Masters® PVC-Pro Medium Grey Cement - 946 mL	12	27.5 lbs	12.5 kg
PVC4L-G	Masters® PVC-Pro Medium Grey Cement - 3.78 L	6	52 lbs	23.5 kg
PVC250-C	Masters® PVC-Pro Medium Clear Cement - 237 mL	24	14.5 lbs	6.5 kg
PVC500-C	Masters® PVC-Pro Medium Clear Cement - 473 mL	24	27.5 lbs	12.5 kg
PVC1L-C	Masters® PVC-Pro Medium Clear Cement - 946 mL	12	27.5 lbs	12.5 kg
PVC4L-C	Masters® PVC-Pro Medium Clear Cement - 3.78 L	6	52 lbs	23.5 kg

*Pooling/puddling can cause weakening and premature failure of the pipe or fitting connection

















Find us on









©2020 CateySCS All Rights Reserved. This information is based on data believed to be reliable but Catey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies All other trademarks can be found on www.oatey.ca.