





DEEP WELL SUBMERSIBLE PUMP

Pumps up to 900 US GPH Maximum Head of 275 Feet

3 WIRE + GROUND / 230V 12 STAGES

PUMP CAPACITY			
HEAD		LPH (JS GPH
275'	84,0m	1760	465
250'	76,0m	2180	575
225'	68,5m	2405	635
200'	61,0m	2615	690
180'	55,0m	2800	740
160'	49,0m	2975	785
140'	43,0m	3145	830
120'	36,5m	3295	870
100'	30,5m	3410	900
	HE/ 275' 250' 225' 200' 180' 160' 140' 120'	HEAD 275' 84,0m 250' 76,0m 225' 68,5m 200' 61,0m 180' 55,0m 160' 49,0m 140' 43,0m 120' 36,5m	HEADLPH 0275'84,0m1760250'76,0m2180225'68,5m2405200'61,0m2615180'55,0m2800160'49,0m2975140'43,0m3145120'36,5m3295

Friction loss in pipe not included

Best efficiency			
Pressure switch set to :	Depth :		
20/40 PSI 30/50 PSI	114' - 198' 91' - 175'		

- Made of non-corrosive 316 stainless steel material

BURCAM

- Precision machined stainless steel impellers and diffusers
- NEMA standard stainless steel interchangeable pump head

Water in

- Hexagonal stainless steel drive shaft

Recommended for homes, cottages and farms for installation in water wells which are 4" or larger in diameter.

Control box included.



WHERE WE ARE ADDRESS OF TAXABLE PARTY.

BURCAM

www.burcam.com

YEAR WARRANTY

10

GPM