Model #SJT050-1


½ HP Shallow Well Jet Pump C/W Pressure Tank



Features & Benefits:

- For use on shallow well applications up to 25ft water level.
- Durable cast iron pump housing.
- Built-in thermal overload protection.
- Fully automatic water supply.
- Dedicated priming port for volute filling.
- 4 1 ¼" NPT suction and 1" NPT discharge.
- Complete with 6 gallon tank.
- 2 year warranty.

| Inlet | NPT1 | | | | | | |
|---------------------|------------------------------------|--|--|--|--|--|--|
| Discharge | NPT1 | | | | | | |
| Pump Cover | / | | | | | | |
| Motor Housing | ZL102 | | | | | | |
| Pump Body | HT200 | | | | | | |
| Switch Type | Press switch | | | | | | |
| Impeller | PPO-GF30 | | | | | | |
| Seal Design | Mechanical seal | | | | | | |
| Seal Material | Graphite & Ceramic | | | | | | |
| Oil Filled Motor | No | | | | | | |
| Power Cord | | | | | | | |
| Net Weight | | | | | | | |
| Gross Weight | | | | | | | |
| Package Size | 197*118*205 | | | | | | |
| Expected Life Cycle | ON 2 SEC OFF 2 sec. 300,000 cycles | | | | | | |
| Motor Wires | Copper | | | | | | |
| Self-Priming | No | | | | | | |
| Certification | CSA | | | | | | |
| | | | | | | | |



| Model | HP Voltage | Voltago | AMP | Discharge NPT(In) | GPH of water @ Total Ft. of Head | | | | | Max.Head Ft |
|----------|------------|------------|-----------|----------------------|----------------------------------|-------|-------|-------|-------|-------------|
| | | voitage | | | 5 ft | 10 ft | 15 ft | 20 ft | 25 ft | Max.neau Ft |
| SJT050-1 | 1/2 | 115 or 230 | 7.2 or3.6 | 1 | 390 | 340 | 280 | 250 | | 147 |

