## **RS9110T**

# Programmable Thermostat Single Stage - 1 Heat / 1 Cool





RS9110T

### Features and Benefits

- · Quick, easy installation
- · Modern, user-friendly design and operation
- 7-day, 5-1-1 or non-programmable
- Large 8.8-square-inch blue backlit touchscreen display
- Auto changeover
- Adjustable temperature differential (swing)







omer Service +1.800.304.6563 HVACCustomerService@robertshaw.com www.robertshaw.com

©2021 Robertshaw 1/21 -150-2800

### Description

Contractors can offer owners easy, yet powerful and reliable single-stage heating and cooling control in a simple, modern design with the RS9110T programmable wall thermostat.

#### Easy installation.

- Large terminal blocks
- Universal sub-base

#### Easy setup.

- Quick-access menu button
- Contractor/technician setup menu
- Easy-to-understand programming menus
- Intuitive wake, leave, return, sleep programming icons

 Factory pre-set energyefficiency program

#### Simple, yet powerful control.

- · Large, easy-to-read 8.8-square-inch blue backlit touchscreen display
- Easy-access front-load battery compartment
- Adjustable temperature differential (swing) for energy optimization and maximum

#### system life

- Auto changeover
- Five-minute selectable on/off compressor delay protection for short-cycling prevention
- Minimum compressor run time
- Filter change reminder
- Keypad lockout

### Designed and built for reliability.

ISO9001-certified

### Specifications

Dimensions (W x H x D)	4.7 x 3.8 x 1 in. (119.6 x 97.6 x 26 mm)
Mounting	Wall or junction box
System compatibility	Single-stage heating and cooling
System fuel source	Gas, electric or oil
Heat pump compatibility	Systems without auxiliary or emergency heat
Millivolt application compatibility	Yes
Temperature range	32°F to 99°F (1°C to 40°C)
Control temperature range	41°F to 90°F (5°C to 32°C)
Display accuracy	±1°C (at 20°C) / ±1°F (at 68°F)
Power sources	24V AC (18 to 30V AC), 50/60 Hz for hardwire (common wire required) or 2 AAA 1.5V alkaline batteries (included)
Terminals	Rh, Rc, C, Y, W, G, O, B

# Replacement Information

RS9110T	
Pro1 <sup>®</sup>	T805
Honeywell	TH6110D1021, TH7220U1035, TH6220U2000, TH6210U2001, TH6220D1002, TH6220D1028
Braeburn®	6100
Emerson™ White-Rodgers™	1F85U-22PR
Aprilaire®	8463