

24 Liter / 6 Gallon Horizontal Water Pressure Tank



PRODUCT INFORMATION

Triple coated tough, appliance-like finish for extended life
 Heavy gauge steel construction for maximum durability
 Stainless steel water connector
 Factory pre-charged at 30 PSI
 Convenient air valve location for quick hook up
 No water to metal contact; rust-free operation
 Air Sealed Diaphragm. NSF certified butyl rubber diaphragm 100%
 Air Seal
 Certified to ANSI/NSF 61

Model Number		HT-24H			
Customer SKU Number					
		FOB	Vaughan, ON		
SPECIFICATIONS		Retail Box Dimensions			
		Inches		Cm	
Tank Orientation	Horizontal	H	13.6	H	34.6
Certified	NSF 61	W	17.1	W	43.5
Color/Finish	Blue	D	11.0	D	30.0
Discharge outlet size	1 inch	Wt. (lb)	11.9	Wt. (kg)	5.4
Outlet Connection size	1 inch	Product Dimensions			
Tank Material	Steel	inches		cm	
Tank Capacity	24L/6Ga	H	12.8	H	32.6
Precharge PSI	40	W	16.3	W	41.5
Maximum Working Pressure	120 PSI	D	11.4	D	29.0
Diameter	29cm/11.4in	Wt. (lb)	10.6	Wt. (kg)	4.8